

OPPAIR

2-IN-1



SCREW AIR COMPRESSOR AIR TANK



EQUIPMENT DISPLAY

www.oppaircompressor.com

Model	OPN-5PV	OPN-7PV	OPN-10PV	OPN-10F
Power(kw)	4	5.5	7.5	7.5
Housepower(hp)	5	7.5	10	10
Air displacement/working pressure(m3/min/bar)	0.67/7	0.98/7	1.2/7	1.2/7
	0.63/8	0.95/8	1.1/8	1.1/8
	0.59/10	0.7/10	0.9/10	0.9/10
	0.52/12	0.6/12	0.8/12	0.8/12
Air Tank(L)	220	220	220	220
Voltage	Single-Phase/3-Phase			3-Phase
Type	PM VSD			Fixed speed
Air outlet diameter	DN20*2	DN20*2	DN20*2	DN20*2
Lubricating oil volume(L)	4-5	4-5	4-5	4-5
Noise level dB(A)	56±2	60±2	60±2	60±2
Driven method	Direct driven			
Smart method	Variable frequency start			Y-▲
Length(mm)	1220	1220	1220	1220
Width(mm)	650	650	650	650
Height(mm) with wheels	1260	1260	1260	1260
Height(mm) without wheels	1150	1150	1150	1150
Weight(kg)	190	200	230	230



SHANDONG OPPAIR MACHINERY MANUFACTURING CO.,LTD

For detailed video, please scan the QR code

